The Department of Ecology does NOT Warranty the Data and/or the Information on this Well Report.

Welltag id: AGA996

STATE OF WASHINGTO.
DEPARTMENT OF CONSERVATION
AND DEVELOPMENT

WELL LOG No. A. 6369 -

Date 8-1- 1962

Record by well driller

Source driller's record

Location: State of WASHINGTON
County Island
Area
Map
¼ ¼ sec. 3 T. 32 N., R. 1 E. WM

Diagram of Section

32/1E-3M
File number

Drilling Co. Lambert Vander Stoep
Address P.O. Box 277, Oak Harbor, Wash.
Method of Drilling Date Dec. 6, 1961
Owner Ward T. Norman
Address Rt. 2, Box 36, Oak Harbor, Wash.
Land surface, datum 160' ±10 ft. above below

Correlation	Material	Thickness (feet)	Depth (feet)
	(Transcribe driller's terminology literally but paraphrase as necessary, in parentheses. If material water-bearing, so state and record static level if reported. Give depths in feet below land-surface datum unless otherwise indicated. Correlate with stratigraphic column, if feasible. Following log of materials, list all casings, perforations, screens, etc.)		
	Sandy hardpan	53	53
	" clay	46	99
	Sand	20	119
	Clay	21	140
	Sand	35	175
	Sandy clay	6	181
	Water sand	22	203
	Still sand at 203 ft.		
	MX PUMP TEST:		
	Dim. 6"x203'		
	SWL: 150 ft. (12-6-61)		
	DD: 15 ft.		
	Yield: 15 g.p.m.		
	Water Temp. 56°		
	Type & size of pump: submersible		
	Type & size of motor or engine:		
	1½ h/p. electric		
	(over)		

Turn up Sheet of sheets

The Department of Ecology does NOT Warranty the Data and/or the Information on this Well Report.

WELL LOG.—Continued No..... ..../.. .....-.....

CORRE-LATION	MATERIAL		THICKNESS (feet)	DEPTH (feet)
		Depth forward	———	
	15 minute recovery			
	CASING:			
	6" diam. Std. casing from 0 to 198 ft.			
	Shoe is 198 deep.			
	PERFORATIONS:			
	5 ft. #10 slot brass screen 198 to 203 ft.			

Department of Ecology does NOT Warranty the Data and/or the Information on this Well Report.

STATE OF WASHINGTO.
DEPARTMENT OF CONSERVATION
AND DEVELOPMENT

WELL LOG No. A. 6369

Date 8-1- , 1962

Record by well driller

Source driller's record

Location State of WASHINGTON

County Island

Area

Map

¼ ¼ sec. 3 T. 32 N., R. 1 E. W.M.

Diagram of Section

Drilling Co. Lambert Vander Stoep

Address P.O. Box 277, Oak Harbor, Wash.

Method of Drilling Date Dec.6 , 1961

Owner Ward T. Norman

Address Rt. 2, Box 36, Oak Harbor, Wash.

Land surface, datum 160'±10 ft. above below

32/1E-3M

File number

CORRELATION	MATERIAL	THICKNESS (feet)	DEPTH (feet)
	Sandy hardpan	53	53
	" clay	46	99
	Sand	20	119
	Clay	21	140
	Sand	35	175
	Sandy clay	6	181
	Water sand	22	203
	Still sand at 203 ft.		
	XX PUMP TEST:		
	Dim. 6"x203'		
	SWL: 150 ft. (12-6-61)		
	DD: 15 ft.		
	Yield: 15 g.p.m.		
	Water Temp. 56°		
	Type & size of pump: submersible		
	Type & size of motor or engine:		
	1½ h/p. electric		
	(over)		

(Transcribe driller's terminology literally but paraphrase as necessary, in parentheses. If material water-bearing, so state and record static level if reported. Give depths in feet below land-surface datum unless otherwise indicated. Correlate with stratigraphic column, if feasible. Following log of materials, list all casings, perforations, screens, etc.)

Turn up

Sheet ... of ... sheets

partment of Ecology does NOT Warranty the Data and/or the Information on this Well Report.

WELL LOG.—Continued No..... ..../.. .....-.....

CORRE-LATION	MATERIAL	THICKNESS (feet)	DEPTH (feet)
	Depth forward	———	
	15 minute recovery		
	CASING:		
	6" diam. Std. casing from 0 to 198 ft.		
	Shoe is 198 deep.		
	PERFORATIONS:		
	5 ft. #10 slot brass screen 198 to 203 ft.		

S F No 7449—OS—6-61—2M