The Department of Ecology does NOT Warranty the Data and/or the Information on this Well Report.

Well tag id: AGA502

STATE OF WASHINGTON
DEPARTMENT OF CONSERVATION
AND DEVELOPMENT

WELL LOG

No. Appli. 724
Cert. 187-A

Date Oct. 16, 1945

Record by

Source Driller's record

Location: State of WASHINGTON

County Island

Area

Map

Lot 2 ¼ ¼ sec. 22 T. 32 N., R. 2 E. W.

DIAGRAM OF SECTION

32N/2E-22T
File number

Drilling Co C. E. Miller

Address 1320 Rucker Ave., Everett, Wn.

Method of Drilling Date 10-14- 1945

Owner A. R. Stephenson

Address Stanwood, Washington

Land surface, datum ft. above / below

Correlation	Material	Thickness (feet)	Depth (feet)
	Hard pan & dry gravel	78	78
	Silty clay & blue clay	32	110
	Tight clay hard pan	45	155
	Med. sand & fine pea gravel	13	168
	Med. to heavy gravel	4	172
	Pump test:		
	Dim: 172' x 8"		
	SWL: 38'		
	DD: 20'		
	Yield: 35 g.p.m.		
	Casing: 8" from 1' to 157'		
	6" " 157' to 172'		
	Perforations:		
	Ed. E. Johnson screen 162' to 168'		
	Slotted pipe 1/8"x4" 168' to 172'		

(Transcribe driller's terminology literally but paraphrase as necessary, in parentheses. If material water-bearing, so state and record static level if reported. Give depths in feet below land-surface datum unless otherwise indicated. Correlate with stratigraphic column, if feasible. Following log of materials, list all casings, perforations, screens, etc.)

Turn up

Sheet ____ of ____ sheets

Department of Ecology does NOT Warranty the Data and/or the Information on this Well Report.

STATE OF WASHINGTON
DEPARTMENT OF CONSERVATION
AND DEVELOPMENT

WELL LOG

No. Appli. 724
Cert. 187-A

Date Oct. 16, 1945

Record by

Source Driller's record

Location: State of WASHINGTON

County Island

Area

Map

Lot 2 ¼ ¼ sec. 22 T. 32 N., R 2 E. W.

DIAGRAM OF SECTION

Drilling Co C. E. Miller

Address 1320 Rucker Ave., Everett, Wn.

Method of Drilling Date 10-14- 1945

Owner A. R. Stephenson

Address Stanwood, Washington

Land surface, datum ft. above below

CORRELATION	MATERIAL	THICKNESS (feet)	DEPTH (feet)
	Hard pan & dry gravel	78	78
	Silty clay & blue clay	32	110
	Tight clay hard pan	45	155
	Med. sand & fine pea gravel	13	168
	Med. to heavy gravel	4	172
	Pump test:		
	Dim: 172' x 8"		
	SWL: 38'		
	DD: 20'		
	Yield: 35 g.p.m.		
	Casing: 8" from 1' to 157'		
	6" " 157' to 172'		
	Perforations:		
	Ed. E. Johnson screen 162' to	168'	
	Slotted pipe 1/8"x4" 168' to	172'	

(Transcribe driller's terminology literally but paraphrase as necessary, in parentheses. If material water-bearing, so state and record static level if reported. Give depths in feet below land-surface datum unless otherwise indicated. Correlate with stratigraphic column, if feasible. Following log of materials, list all casings, perforations, screens, etc.)

Turn up

Sheet ____ of ____ sheets

32N/2E-22T
File number